

ENSTO

PRODUCT SPECIFICATION

2024-05-06



6438389016840

STE3.2

Code	STE3.2
GTIN	6438389016840
Name	
Description	The additional sheath sealing kit is used to provide longitudinal waterblocking inside of the cable sheath when jointing wetted non-waterblocked 3-core Cu-wire shielded cables. The kit is suitable for max. 24 kV XLPE insulated cables with Cu-wire shield. The kit contains an insulating heat shrink breakout and sealing mastic.
Vendor	Ensto Finland Oy



Teknisk specifikation

Features

Shrink technique:	Heat shrink
Accessory type:	Additional kit
Conductor size round:	25 ... 240 mm ²

Cable

Conductor size Um = 12 kV:	35 ... 240 mm ²
Conductor size Um = 24 kV:	25 ... 150 mm ²
Material insulation:	Polymeric
Material screen/shield:	Cu-wire
Number of cores:	3

Others

ETIM Class:	EC003520
-------------	----------

Dimensions

Weight:	0,382 kg
---------	----------

ETIM Teknisk specifikation

etim

Number of cores:	3
Type of cable termination:	Heat-shrink
Material insulating material:	Other

Förpackning

Plastic bag

Paketstorlek:	1 pce
Djup:	10 mm
Bredd:	230 mm
Höjd:	350 mm
Vikt:	0,391 kg
Volym:	0,805 l

Carton (Standardpaket)

Paketstorlek:	5 pcs
Djup:	398 mm
Bredd:	263 mm
Höjd:	221 mm
Vikt:	2,229 kg
Volym:	23,132954 l

Pallpaket

Paketstorlek:	180 pcs
Djup:	1200 mm
Bredd:	800 mm
Höjd:	1054 mm
Vikt:	100,244 kg
Volym:	1011,84 l